

**Magnetic contact  
MK30 in a set with surface-mount housing**

Art. No.	Color	Cable length
<b>100091712</b>	<b>White</b>	<b>2.5 m</b>

**VdS class B (G 104511) Monitoring for opening**

The magnetic contact MK30 is used for monitoring of doors, windows, distributors, etc. for opening. MK30 comprises a reed switch in a cylindrical plastic housing and a rod magnet. For surface mounting, there are 2 surface-mount housings and 2 spacer blocks each of 2.5 mm and 5 mm in this set.

- Connection cable, 4 x 0.14 mm<sup>2</sup> with same-color insulated wires
- Connection cable for LSA-Plus connection technology
- Cable Ø 4 mm
- Environmental class in compliance with VdS 2110 class II
- Operating temperature -25 °C to +60 °C
- Degree of protection IP68
- Dimensions of contact (ØxL) 6x30 mm
- Dimensions of magnet (ØxL) 6x30 mm
- Dimensions of surface-mount housing (WxHxD) 48x12.5x9.5 mm
- Contact load 30 V / 0.1 A

**Z**

980090760 Sheet metal screw with oval head, DIN 7981 A2, Dimensions 2.9x9.5 mm, Pack of 1000 pcs.

980090761 Sheet metal screw with oval head, DIN 7981 A2, Dimensions 2.9x13 mm, Pack of 1000 pcs.

980090762 Sheet metal screw with oval head, DIN 7981 A2, Dimensions 2.9x19 mm, Pack of 1000 pcs.